

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 03/23/2015 Revision date: 10/01/2019 Version: 2.0

### **SECTION 1: Identification**

Identification

: CUCUMBER MELON MB9000 Product name

Product code 1788365 SKU# FG750366

Recommended use and restrictions on use 1.2.

Use of the substance/mixture : Aerosol

For professional use only

Odour agents Air care products

Recommended use Air care products, Odour agents

Professional uses: Public domain (administration, education, entertainment, services, Restrictions on use

1.3. Supplier

Manufacturer

Rubbermaid Commercial Products LLC 3124 Valley Avenue Winchester, VA 22601-2694 - USA

T 1.800.347.9800

www.rubbermaidcommercial.com

Other

Rubbermaid Commercial Products LLC 20 Hereford Street Brampton, ON L6Y 0M1 - Canada

T 1.800.998.7004

**Emergency telephone number** 

Emergency number : 24-Hour Emergency - INFOTRAC: 1-800-535-5053 (Domestic) | 1-352-323-3500 (International)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

### **GHS-US** classification

Flammable aerosols, H222 Extremely flammable aerosol.

Category 1

Gases under pressure : H280 Contains gas under pressure; may explode if heated.

Compressed gas

Skin corrosion/irritation, H315

Category 2

Serious eye damage/eye H319

irritation, Category 2

Skin sensitisation, Category H317

Specific target organ H335

toxicity — Single exposure, Category 3, Respiratory

tract irritation

Full text of H statements: see section 16

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

### GHS Label elements, including precautionary statements

### **GHS US labelling**

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) H222 - Extremely flammable aerosol.

H280 - Contains gas under pressure; may explode if heated.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation.

Precautionary statements (GHS US) P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

06/15/2020 EN (English) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing vapours, spray, mist.

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves.

P302+P352 - If on skin: Wash with plenty of water.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a doctor if you feel unwell.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Alcohol	(CAS-No.) 64-17-5	20 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
HEXYLENE GLYCOL	(CAS-No.) 107-41-5	10 – 20	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
LINALOOL	(CAS-No.) 78-70-6	1 – 10	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
METHYLENEDIOXYPHENYL METHYLPROPANAL	(CAS-No.) 1205-17-0	0.1 – 1	Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

### **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Cough. Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

First-aid measures after skin contact : Take off immediately all contaminated clothing. Get medical advice if skin irritation persists. Wash with plenty of water/.... Wash contaminated clothing before reuse.

Rinse cautiously with water for several minutes. Direct contact with the eyes is likely to be

irritating. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

: Causes serious eve irritation.

## 4.2. Most important symptoms and effects (acute and delayed)

Potential adverse human health effects and

: Based on available data, the classification criteria are not met.

symptoms

Symptoms/effects after inhalation : Shortness of breath. May cause an allergic skin reaction. May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

Symptoms/effects after eye contact

First-aid measures after eye contact

06/15/2020 EN (English) 2/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand. Water spray.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

Explosion hazard : May form flammable/explosive vapour-air mixture. Heat may build pressure, rupturing closed

containers, spreading fire and increasing risk of burns and injuries.

Reactivity : Stable under normal conditions of use.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment. DO NOT fight fire when

fire reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove

ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate spillage area. Soak up spills with inert solids, such as clay or diatomaceous earth as

soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

#### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Hazardous waste

due to potential risk of explosion. Do not pierce or burn, even after use.

Precautions for safe handling : No open flames. No smoking. Use only non-sparking tools. Wash hands and other exposed

areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not spray on an

open flame or other ignition source.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated

work clothing should not be allowed out of the workplace. Wash contaminated clothing before

reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Maintain air gap between stacks/pallets. Ground/bond container and receiving equipment.

Comply with applicable regulations. Proper grounding procedures to avoid static electricity

should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight,

Heat sources, Ignition sources. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

06/15/2020 EN (English) 3/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LINALOOL (78-70-6)		
DNEL	DNEL 2.8 mg/m³	
Alcohol (64-17-5)		
DNEL	DNEL	950 mg/m³
ACGIH	Local name	Ethanol
ACGIH	ACGIH STEL (ppm)	1000 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
HEXYLENE GLYCOL (	107-41-5)	
DNEL	DNEL	14 mg/m³
ACGIH	Local name	Hexylene glycol
ACGIH	ACGIH TWA (ppm)	25 ppm (V - Vapor fraction)
ACGIH	ACGIH STEL (mg/m³)	10 mg/m³ (I - Inhalable particulate matter, H - Aerosol only)
ACGIH	ACGIH STEL (ppm)	50 ppm (V - Vapor fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr
ACGIH	Regulatory reference	ACGIH 2019
METHYLENEDIOXYPH	IENYL METHYLPROPANAL (1205-17-0)	
Not applicable		

### 8.2. Appropriate engineering controls

Appropriate engineering controls

: Provide local exhaust or general room ventilation to minimize mist and/or vapour concentrations.

### 8.3. Individual protection measures/Personal protective equipment

### Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

None under normal use

Respiratory protection:

None under normal use

Other information:

Do not eat, drink or smoke during use.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear Transparent Liquid.

: colourless to slightly yellow

: characteristic

Odour threshold : No data available pH : No data available

06/15/2020 EN (English) 4/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butylacetate=1) : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Vapour pressure : 4.5 - 5.5 bar Relative vapour density at 20 °C : No data available

Relative density : 0.7

: No data available Solubility Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available : No data available Viscosity, kinematic : No data available Viscosity, dynamic No data available Explosive limits Explosive properties : No data available No data available Oxidising properties

#### 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Stable under normal conditions of use.

#### 10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

### 10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

May release flammable gases. fume. Carbon monoxide. Carbon dioxide.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg
LD50 dermal rabbit	> 16000 mg/kg
LC50 inhalation rat (mg/l)	> 20 mg/l/4h
ATE US (oral)	7060 mg/kg bodyweight

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

06/15/2020 EN (English) 5/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity : Not classified

Based on available data, the classification criteria are not met

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : Shortness of breath. May cause an allergic skin reaction. May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

LINALOOL (78-70-6)	
LC50 fish 1	27.8 mg/l
EC50 other aquatic organisms 1	20 mg/l waterflea
EC50 other aquatic organisms 2	88.3 mg/l
Alcohol (64-17-5)	
LC50 fish 1	13000 mg/l
EC50 Daphnia 1	9300 mg/l
EC50 other aquatic organisms 1	5012 mg/l waterflea
EC50 other aquatic organisms 2	275 mg/l
HEXYLENE GLYCOL (107-41-5)	
LC50 fish 1	8690 mg/l
EC50 other aquatic organisms 1	5410 mg/l waterflea
EC50 other aquatic organisms 2	> 429 ma/l

### 12.2. Persistence and degradability

CUCUMBER MELON MB9000		
Persistence and degradability Not established.		
Alcohol (64-17-5)		
Persistence and degradability	Not established.	

### 12.3. Bioaccumulative potential

CUCUMBER MELON MB9000		
Bioaccumulative potential	Not established.	
LINALOOL (78-70-6)		
Partition coefficient n-octanol/water (Log Pow) 2.84		
Alcohol (64-17-5)		
Partition coefficient n-octanol/water (Log Pow)	-0.32	
Bioaccumulative potential	Not established.	
HEXYLENE GLYCOL (107-41-5)		
Partition coefficient n-octanol/water (Log Pow)	-0.1	

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the ozone layer : None to our knowledge

06/15/2020 EN (English) 6/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Avoid release to the environment.

### **SECTION 13: Disposal considerations**

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use.

Additional information : Handle empty containers with care because residual vapours are flammable. Flammable

vapours may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

### **SECTION 14: Transport information**

### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN1950 Aerosols, 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Other information : No supplementary information available.

#### **Transportation of Dangerous Goods**

Not applicable

### Transport by sea

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1

UN-No. (IMDG) : 1950

Proper Shipping Name (IMDG) : AEROSOLS

Class (IMDG) : 2 - Gases

Limited quantities (IMDG) : SP277

### Air transport

Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1

UN-No. (IATA) : 1950

Proper Shipping Name (IATA) : Aerosols, flammable

Class (IATA) : 2

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

06/15/2020 EN (English) 7/9

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### LINALOOL (78-70-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Alcohol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### **HEXYLENE GLYCOL (107-41-5)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### **METHYLENEDIOXYPHENYL METHYLPROPANAL (1205-17-0)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

#### **CANADA**

#### LINALOOL (78-70-6)

Listed on the Canadian DSL (Domestic Substances List)

#### Alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

#### **HEXYLENE GLYCOL (107-41-5)**

Listed on the Canadian DSL (Domestic Substances List)

### **METHYLENEDIOXYPHENYL METHYLPROPANAL (1205-17-0)**

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

### **National regulations**

#### Alcohol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

### Alcohol (64-17-5)

U.S. - Pennsylvania - RTK (Right to Know) List

#### **HEXYLENE GLYCOL (107-41-5)**

U.S. - Pennsylvania - RTK (Right to Know) List

### **SECTION 16: Other information**

Revision date

Other information

: 10/01/2019

: REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. None.

06/15/2020 EN (English) 8/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-statements:

H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H280	Contains gas under pressure; may explode if heated.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H335	May cause respiratory irritation.	
H411	Toxic to aquatic life with long lasting effects.	

### Indication of changes:

Section	Changed item	Change	Comments
	Precautionary statements (GHS US)	Modified	
	Hazard statements (GHS US)	Modified	
	Hazard pictograms (GHS US)	Modified	
	Revision date	Added	
2.1	GHS-US classification	Modified	

SDS\_US\_GHS\_HazCom\_2012 Newell nieuw

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

06/15/2020 EN (English) 9/9