

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 04/21/2015 Revision date: 10/01/2019 Version: 2.0

SECTION 1: Identification

Identification

: COUNTRY DELIGHT STD AEROSOL Product name

Product code 1821656 SKU# FG4015061

Recommended use and restrictions on use

Use of the substance/mixture : Aerosol

> Air care products Odour agents

For professional use only

Recommended use Air care products, Odour agents

Professional uses: Public domain (administration, education, entertainment, services, Restrictions on use

1.3. Supplier

Manufacturer

Rubbermaid Commercial Products LLC 3124 Valley Avenue Winchester, VA 22601-2694 - USA

T 1.800.347.9800

www.rubbermaidcommercial.com

Other

Rubbermaid Commercial Products LLC 20 Hereford Street

Brampton, ON L6Y 0M1 - Canada

T 1.800.998.7004

Emergency telephone number

Emergency number : 24-Hour Emergency - INFOTRAC: 1-800-535-5053 (Domestic) | 1-352-323-3500 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable aerosols, H222 Extremely flammable aerosol.

Category 1

Gases under pressure : H280

Compressed gas

Skin corrosion/irritation, H315 Causes skin irritation.

Category 2

Serious eye damage/eye H319

irritation. Category 2A

Skin sensitisation, Category H317

Specific target organ H336

toxicity — Single exposure,

Category 3, Narcosis

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) H222 - Extremely flammable aerosol.

H280 - Contains gas under pressure; may explode if heated.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P211 - Do not spray on an open flame or other ignition source.

06/16/2020 EN (English) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing vapours, spray, mist.

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves.

P302+P352 - If on skin: Wash with plenty of water.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a doctor if you feel unwell.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Acetone	(CAS-No.) 67-64-1	20 – 50	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
HEXYLENE GLYCOL	(CAS-No.) 107-41-5	10 – 20	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
BENZYL SALICYLATE	(CAS-No.) 118-58-1	0.1 – 1	Skin Sens. 1, H317
EUGENOL	(CAS-No.) 97-53-0	0.1 – 1	Eye Irrit. 2A, H319 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Cough. Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

First-aid measures after skin contact : Take off immediately all contaminated clothing. Get medical advice if skin irritation persists. Wash with plenty of water/.... Wash contaminated clothing before reuse.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Direct contact with the eyes is likely to be

irritating. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : Shortness of breath. May cause an allergic skin reaction. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

06/16/2020 EN (English) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

Explosion hazard : May form flammable/explosive vapour-air mixture. Heat may build pressure, rupturing closed

containers, spreading fire and increasing risk of burns and injuries.

Reactivity : Stable under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment. DO NOT fight fire when

fire reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove

ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate spillage area. Soak up spills with inert solids, such as clay or diatomaceous earth as

soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Hazardous waste

due to potential risk of explosion. Do not pierce or burn, even after use.

Precautions for safe handling : No open flames. No smoking. Use only non-sparking tools. Wash hands and other exposed

areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not spray on an

open flame or other ignition source. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Contaminated work clothing should not be allowed out of the

workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight,

Heat sources, Ignition sources. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HEXYLENE GLYCOL (107-41-5)		
DNEL	DNEL	14 mg/m³
ACGIH	Local name	Hexylene glycol
ACGIH	ACGIH TWA (ppm)	25 ppm (V - Vapor fraction)
ACGIH	ACGIH STEL (mg/m³)	10 mg/m³ (I - Inhalable particulate matter, H - Aerosol only)

06/16/2020 EN (English) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HEXYLENE GLYCOL (107-41-5)			
ACGIH	ACGIH STEL (ppm)	50 ppm (V - Vapor fraction)	
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr	
ACGIH	Regulatory reference	ACGIH 2019	
Acetone (67-64-1)			
DNEL	DNEL	2110 mg/m³	
ACGIH	Local name	Acetone	
ACGIH	ACGIH TWA (ppm)	250 ppm	
ACGIH	ACGIH STEL (ppm)	500 ppm	
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI	
ACGIH	Regulatory reference	ACGIH 2019	
OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
EUGENOL (97-53-0)			
DNEL	DNEL	36 mg/m³	
BENZYL SALICYLATE (118-58-1)			
Not applicable			

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation to minimize mist and/or vapour

concentrations.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

None under normal use

Respiratory protection:

None under normal use

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear Transparent Liquid.

: colourless to slightly yellow

characteristic

Odour threshold : No data available pH : No data available Melting point : No data available Freezing point : No data available Boiling point : No data available Flash point : No data available Flash point : No data available

06/16/2020 EN (English) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butylacetate=1) : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Vapour pressure : 4.5 - 5.5 bar Relative vapour density at 20 °C : No data available

Relative density : 0.7

Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available : No data available Decomposition temperature : No data available Viscosity, kinematic Viscosity, dynamic : No data available Explosive limits : 1.8 - 19 vol % Explosive properties : No data available : No data available Oxidising properties

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

May release flammable gases. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Acetone (67-64-1)	
ATE US (dust,mist)	50100 mg/l/4h
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
Carcinogenicity	Not classified

EUGENOL (97-53-0)		
IARC group	3 - Not classifiable	
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met	
STOT-single exposure	: May cause drowsiness or dizziness.	
STOT-repeated exposure	: Not classified	
00/40/0000		E/0

06/16/2020 EN (English) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard : Not classified

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : Shortness of breath. May cause an allergic skin reaction. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

HEXYLENE GLYCOL (107-41-5)			
LC50 fish 1	8690 mg/l		
EC50 other aquatic organisms 1	5410 mg/l waterflea		
EC50 other aquatic organisms 2	> 429 mg/l		
Acetone (67-64-1)	Acetone (67-64-1)		
LC50 fish 1	5540 mg/l		
EC50 other aquatic organisms 1	12600 mg/l waterflea		
EC50 other aquatic organisms 2	3400 mg/l		
EUGENOL (97-53-0)			
LC50 fish 1	5.6 mg/l		
EC50 other aquatic organisms 1	1.9 mg/l waterflea		
EC50 other aquatic organisms 2	15.4 mg/l		

12.2. Persistence and degradability

COUNTRY DELIGHT STD AEROSOL		
Persistence and degradability Not established.		
Acetone (67-64-1)		
Persistence and degradability	Not established.	

12.3. Bioaccumulative potential

COUNTRY DELIGHT STD AEROSOL		
Bioaccumulative potential	Not established.	
HEXYLENE GLYCOL (107-41-5)		
Partition coefficient n-octanol/water (Log Pow)	-0.1	
Acetone (67-64-1)		
Partition coefficient n-octanol/water (Log Pow)	-0.24	
Bioaccumulative potential	Not established.	
EUGENOL (97-53-0)		
Partition coefficient n-octanol/water (Log Pow)	2.27	

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : None to our knowledge

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

06/16/2020 EN (English) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: Handle empty containers with care because residual vapours are flammable. Flammable Additional information

vapours may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols, 2.1

UN-No.(DOT) : UN1950 Proper Shipping Name (DOT) : Aerosols

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

: 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except **DOT Vessel Stowage Other**

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

: No supplementary information available. Other information

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1

UN-No. (IMDG) : 1950 : AEROSOLS Proper Shipping Name (IMDG) Class (IMDG) : 2 - Gases Limited quantities (IMDG) : SP277

Air transport

: UN 1950 Aerosols, flammable, 2.1 Transport document description (IATA)

UN-No. (IATA)

Proper Shipping Name (IATA) : Aerosols, flammable

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

HEXYLENE GLYCOL (107-41-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

06/16/2020 EN (English) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)

Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory

EUGENOL (97-53-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

BENZYL SALICYLATE (118-58-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

HEXYLENE GLYCOL (107-41-5)

Listed on the Canadian DSL (Domestic Substances List)

EUGENOL (97-53-0)

Listed on the Canadian DSL (Domestic Substances List)

BENZYL SALICYLATE (118-58-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

HEXYLENE GLYCOL (107-41-5)

U.S. - Pennsylvania - RTK (Right to Know) List

Acetone (67-64-1)

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date

: 10/01/2019

Other information

: REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. None.

Full text of H-statements:

H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H280	Contains gas under pressure; may explode if heated.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	

06/16/2020 EN (English) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Indication of changes:

Section	Changed item	Change	Comments
	Precautionary statements (GHS US)	Modified	
	Revision date	Added	
	Hazard pictograms (GHS US)	Modified	
	Hazard statements (GHS US)	Modified	
2.1	GHS-US classification	Modified	

SDS_US_GHS_HazCom_2012 Newell nieuw

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

06/16/2020 EN (English) 9/9