



TECHNICAL CONCEPTS

BLUE SPLASH MB9000

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 07/14/2014

Revision date: 03/09/2020

Version: 2.0

SECTION 1: Identification

1.1. Identification

Product name : BLUE SPLASH MB9000
Product code : 1830283
SKU # : FG402354

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Air care products
Aerosol
For professional use only
Odour agents
Recommended use : Air care products, Odour agents
Restrictions on use : Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

1.3. Supplier

Manufacturer

Rubbermaid Commercial Products LLC
3124 Valley Avenue
Winchester, VA 22601-2694 - USA
T 1.800.347.9800
www.rubbermaidcommercial.com

Other

Rubbermaid Commercial Products LLC
20 Hereford Street
Brampton, ON L6Y 0M1 - Canada
T 1.800.998.7004

1.4. Emergency telephone number

Emergency number : 24-Hour Emergency - INFOTRAC: 1-800-535-5053 (Domestic) | 1-352-323-3500 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable aerosols, Category 1	H222	Extremely flammable aerosol.
Gases under pressure : Compressed gas	H280	Contains gas under pressure; may explode if heated.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation.

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H222 - Extremely flammable aerosol.
H280 - Contains gas under pressure; may explode if heated.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.

Precautionary statements (GHS US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

BLUE SPLASH MB9000

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing vapours, spray, mist.
P264 - Wash hands thoroughly after handling.
P280 - Wear protective clothing.
P302+P352 - If on skin: Wash with plenty of Water.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a doctor if you feel unwell.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Alcohol	(CAS-No.) 64-17-5	20 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
HEXYLENE GLYCOL	(CAS-No.) 107-41-5	10 – 20	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
2,6-DIMETHYL-7-OCTEN-2-OL	(CAS-No.) 18479-58-8	1 – 10	Eye Irrit. 2A, H319
hexyl 2-hydroxybenzoate	(CAS-No.) 6259-76-3	0.1 – 1	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
LIMONENE	(CAS-No.) 5989-27-5	0.1 – 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Cough. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact : Wash with plenty of water/.... Get medical advice if skin irritation persists. Wash contaminated clothing before reuse. Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Direct contact with the eyes is likely to be irritating. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation : Shortness of breath. May cause an allergic skin reaction.
Symptoms/effects after skin contact : Causes skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.

BLUE SPLASH MB9000

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Reactivity : Stable under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate spillage area. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Do not pierce or burn, even after use.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not spray on an open flame or other ignition source.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources, Ignition sources. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

BLUE SPLASH MB9000

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LIMONENE (5989-27-5)		
Not applicable		
Alcohol (64-17-5)		
DNEL	DNEL	950 mg/m ³
ACGIH	Local name	Ethanol
ACGIH	ACGIH STEL (ppm)	1000 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
HEXYLENE GLYCOL (107-41-5)		
DNEL	DNEL	14 mg/m ³
ACGIH	Local name	Hexylene glycol
ACGIH	ACGIH TWA (ppm)	25 ppm (V - Vapor fraction)
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only)
ACGIH	ACGIH STEL (ppm)	50 ppm (V - Vapor fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr
ACGIH	Regulatory reference	ACGIH 2019
2,6-DIMETHYL-7-OCTEN-2-OL (18479-58-8)		
Not applicable		
hexyl 2-hydroxybenzoate (6259-76-3)		
Not applicable		

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation to minimize mist and/or vapour concentrations.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

None under normal use

Respiratory protection:

None under normal use

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear Transparent Liquid.
: Colourless light yellow
: characteristic

BLUE SPLASH MB9000

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: 3.5 – 4.5 bar
Relative vapour density at 20 °C	: No data available
Relative density	: 0.619 – 0.645
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: 1.8 – 19 vol %
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg
LD50 dermal rabbit	> 16000 mg/kg
LC50 inhalation rat (mg/l)	> 20 mg/l/4h
ATE US (oral)	7060 mg/kg bodyweight

hexyl 2-hydroxybenzoate (6259-76-3)	
LD50 oral rat	> 5000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.

BLUE SPLASH MB9000

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

LIMONENE (5989-27-5)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified
STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : Shortness of breath. May cause an allergic skin reaction.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Alcohol (64-17-5)

LC50 fish 1	13000 mg/l
EC50 Daphnia 1	9300 mg/l
EC50 other aquatic organisms 1	5012 mg/l waterflea
EC50 other aquatic organisms 2	275 mg/l

HEXYLENE GLYCOL (107-41-5)

LC50 fish 1	8690 mg/l
EC50 other aquatic organisms 1	5410 mg/l waterflea
EC50 other aquatic organisms 2	> 429 mg/l

12.2. Persistence and degradability

BLUE SPLASH MB9000

Persistence and degradability	Not established.
-------------------------------	------------------

Alcohol (64-17-5)

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

BLUE SPLASH MB9000

Bioaccumulative potential	Not established.
---------------------------	------------------

Alcohol (64-17-5)

Partition coefficient n-octanol/water (Log Pow)	-0.32
Bioaccumulative potential	Not established.

HEXYLENE GLYCOL (107-41-5)

Partition coefficient n-octanol/water (Log Pow)	-0.1
---	------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : None to our knowledge

BLUE SPLASH MB9000

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapours may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols
flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1

UN-No. (IMDG) : 1950

Proper Shipping Name (IMDG) : AEROSOLS

Class (IMDG) : 2 - Gases

Limited quantities (IMDG) : SP277

Air transport

Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1

UN-No. (IATA) : 1950

Proper Shipping Name (IATA) : Aerosols, flammable

Class (IATA) : 2

BLUE SPLASH MB9000

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

LIMONENE (5989-27-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Alcohol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

HEXYLENE GLYCOL (107-41-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2,6-DIMETHYL-7-OCTEN-2-OL (18479-58-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

hexyl 2-hydroxybenzoate (6259-76-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

LIMONENE (5989-27-5)

Listed on the Canadian DSL (Domestic Substances List)

Alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

HEXYLENE GLYCOL (107-41-5)

Listed on the Canadian DSL (Domestic Substances List)

2,6-DIMETHYL-7-OCTEN-2-OL (18479-58-8)

Listed on the Canadian DSL (Domestic Substances List)

hexyl 2-hydroxybenzoate (6259-76-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Alcohol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Alcohol (64-17-5)

U.S. - Pennsylvania - RTK (Right to Know) List

HEXYLENE GLYCOL (107-41-5)

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 03/09/2020

BLUE SPLASH MB9000

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information

: REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. None.

Full text of H-statements:

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Indication of changes:

Section	Changed item	Change	Comments
	Precautionary statements (GHS US)	Modified	
	Revision date	Added	
	Hazard pictograms (GHS US)	Modified	
	Hazard statements (GHS US)	Modified	
2.1	GHS-US classification	Modified	

SDS_US_GHS_HazCom_2012 Newell nieuw

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.