

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 4/2/2020 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture

Product name : Pure CirculAir 90 SKU # : FG402498

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Air care products,Odour agents

Recommended use : Air care products, Odour agents, Professional uses: Public domain (administration, education,

entertainment, services, craftsmen)

Restrictions on use : Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

1.4. Supplier's details

Manufacturer Other

Rubbermaid Commercial Products LLC Rubbermaid Commercial Products LLC

3124 Valley Avenue 20 Hereford Street
Winchester, VA 22601-2694 Brampton, ON L6Y 0M1

A Canada

T 1.800.347.9800 T 1.800.998.7004 www.rubbermaidcommercial.com

1.5. Emergency phone number

Emergency number : 24-Hour Emergency - INFOTRAC: 1-800-535-5053 (Domestic) | 1-352-323-3500 (International)

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquid, Category 3

Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 2

H315

Causes skin irritation.

Causes serious eye irritation.

Skin sensitization, Category 1

H317

May cause an allergic skin reaction.

Full text of H-statements: see section 16

2.2. Label elements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P280 - Wear eye protection, protective gloves.

P301+P310 - If swallowed: Immediately call a POISON CENTER.

 ${\tt P303+P361+P353-If\ on\ skin\ (or\ hair):\ Take\ off\ immediately\ all\ contaminated\ clothing.\ Rinse}$

skin with water/shower.

P331 - Do NOT induce vomiting.

P370+P378 - In case of fire: Use appropriate media to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of an approved waste disposal plant to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Ethanol	CAS-No.: 64-17-5	10 – 20	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
3-butoxypropan-2-ol; propylene glycol monobutyl ether	CAS-No.: 5131-66-8	0.1 – 2.9	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Cedarwood Oil	CAS-No.: 8000-27-9	1 – 10	Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Clove Oil	CAS-No.: 8000-34-8	< 1	Flam. Liq. 3, H226 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Take off immediately all contaminated clothing. Rinse skin with water/shower.

4/2/2020 (Issue date) US - en 2/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms/effects, acute and delayed

Potential adverse human health effects and

symptoms

: May cause an allergic skin reaction.

: Based on available data, the classification criteria are not met.

Symptoms/effects after skin contact Symptoms/effects after ingestion

: Risk of lung oedema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide.

Unsuitable extinguishing media : Water.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective

equipment. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No

smoking.

For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel. Ventilate spillage area. No open flames, no sparks, and no

smoking.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Environmental precautions : Prevent liquid from entering sewers, watercourses, underground or low areas. Avoid release to

the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Notify authorities if product enters sewers or public waters. Take up liquid spill into absorbent

material.

See Section 8,Exposure controls and personal protection

4/2/2020 (Issue date) US - en 3/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Take precautionary measures against static discharge. Use only non-sparking tools.

Ground/bond container and receiving equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure good ventilation of the work station. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear

personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Ground/bond container and receiving equipment. Does not require any specific or particular

technical measures.

Storage conditions : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Incompatible products : Strong acids. Oxidizing agent.

Incompatible materials : Heat sources. Direct sunlight. Sources of ignition.

Storage temperature : 4 - 29 °C

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Pure CirculAir 90		
USA - ACGIH - Occupational Exposure Limits		
Local name	Ethanol	
ACGIH® TLV® STEL	1880 mg/m³	
	1000 ppm	
Remark (ACGIH®)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)	
egulatory reference ACGIH 2025		
USA - OSHA - Occupational Exposure Limits		
Local name	Ethyl alcohol (Ethanol)	
OSHA PEL TWA	1900 mg/m³	
	1000 ppm	
Regulatory reference (US-OSHA)	S-OSHA) OSHA Annotated Table Z-1	
Ethanol (64-17-5)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Ethanol	
ACGIH® TLV® STEL	1880 mg/m³	
	1000 ppm	
Remark (ACGIH®)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)	
Regulatory reference	ACGIH 2025	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol (64-17-5)	
USA - OSHA - Occupational Exposure Limits	
Local name Ethyl alcohol (Ethanol)	
OSHA PEL TWA	1900 mg/m³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid

Appearance : colourless to slightly yellow.

Colour: ColourlessOdour: characteristicOdour threshold: No data availablepH: No data availableMelting point: No data availableFreezing point: No data available

Boiling point : $\approx 80 \, ^{\circ}\text{C}$

Flash point : \approx 37 °C Closed cup

Flammability (solid, gas) : Flammable liquid and vapour.

Vapour pressure : No data available Relative vapour density at 20°C : No data available

Relative density : ≈ 0.89

Solubility : insoluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, kinematic : ≈ 3.3 mm²/s

Explosive limits : No data available

Particle characteristics : No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition. Heat. Avoid contact with hot surfaces.

10.5. Incompatible materials

Strong acids. Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethanol (64-17-5)		
LD50 oral rat	7060 mg/kg	
LD50 oral	10470 mg/kg bodyweight	
LD50 dermal rabbit	> 16000 mg/kg	
LD50 dermal	15800 mg/kg bodyweight	
LC50 Inhalation - Rat	> 20 mg/l/4h	
LC50 Inhalation - Rat (Dust/Mist)	> 99999 mg/l	
ATE US (oral)	7060 mg/kg bodyweight	

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

4/2/2020 (Issue date) US - en 6/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-single exposure : Not classified

Ethanol (64-17-5)

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Pure CirculAir 90

Viscosity, kinematic ≈ 3.3 mm²/s

Potential adverse human health effects and

......

symptoms
Symptoms/effects after skin contact

: May cause an allergic skin reaction.

: Based on available data, the classification criteria are not met.

Symptoms/effects after ingestion : Risk of lung oedema.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Ethanol (64-17-5)	
LC50 - Fish [1]	13000 mg/l
EC50 - Crustacea [1]	9300 mg/l
EC50 - Other aquatic organisms [1]	5012 mg/l waterflea
EC50 - Other aquatic organisms [2]	275 mg/l

12.2. Persistence and degradability

Pure CirculAir 90		
Persistence and degradability	Not established.	
Ethanol (64-17-5)		
Persistence and degradability Not established.		
3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)		
Persistence and degradability Rapidly degradable		
Clove Oil (8000-34-8)		
Persistence and degradability	Rapidly degradable	
Cedarwood Oil (8000-27-9)		

12.3. Bioaccumulative potential

Persistence and degradability

Pure CirculAir 90		
Bioaccumulative potential	Not established.	
Ethanol (64-17-5)		
Partition coefficient n-octanol/water (Log Pow)	-0.32	

Rapidly degradable

4/2/2020 (Issue date) US - en 7/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol (64-17-5)

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

Other information : Avoid release to the environment.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to hazardous or special waste collection point, in accordance with local,

regional, national and/or international regulation.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecological waste information : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN Number

UN-No. (DOT) : UN1993 UN-No. (TDG) : Not applicable

UN-No. (IMDG) : 1993 UN-No. (IATA) : 1993

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Proper Shipping Name (TDG) : Not applicable

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S. Proper Shipping Name (IATA) : Flammable liquid, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3 Hazard labels (DOT) : 3



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3

4/2/2020 (Issue date) US - en 8/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : Not applicable

Packing group (IMDG) : III
Packing group (IATA) : III

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN1993

DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the

bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

: 220 L

4/2/2020 (Issue date) US - en 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

TDG

Not applicable

IMDG

Special provisions (IMDG) : 223, 274, 955

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) : A

IATA

Special provisions (IATA) : A3 PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y344 PCA limited quantity max net quantity (IATA) : 10L PCA packing instructions (IATA) : 355 PCA max net quantity (IATA) : 60L CAO packing instructions (IATA) : 366 CAO max net quantity (IATA) : 220L ERG code (IATA) : 3L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

3-butoxypropan-2-ol; propylene glycol monobutyl ether (5131-66-8)

Listed on the Canadian DSL (Domestic Substances List)

Clove Oil (8000-34-8)

Listed on the Canadian DSL (Domestic Substances List)

Cedarwood Oil (8000-27-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations	
Ethanol(64-17-5)	U.S Pennsylvania - RTK (Right to Know) List	

SECTION 16 Other Information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date : 4/2/2020

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Other information : None.

Full text of hazard classes and H-statements		
H225	Highly flammable liquid and vapour	
H226	Flammable liquid and vapour	
H304	May be fatal if swallowed and enters airways	
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H319	Causes serious eye irritation	
H335	May cause respiratory irritation	
H411	Toxic to aquatic life with long lasting effects	

Indication of changes:		
Section	Changed item	Comments
2	GHS-US classification	Modified
2.2	Hazard pictograms (GHS US)	Removed Per our supplier the Health Hazard pictogram can be removed. They based their decision on a classification change from one of their suppliers.
3	Composition/information on ingredients	Modified

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.